

## US 62-US 251

### SUBMERSIBLE DRAINAGE PUMPS



- 10 mm free passage
- Run dry protection
- Controllable oil chamber
- SiC mechanical seal
- independent of sense of rotation
- Replaceable moisture sealed cable inlet

#### DESCRIPTION

The centrifugal submersible drainage pumps US 62-251 can be used wherever sewage water with solids up to 10 mm particle size occurs, e.g. in collecting sumps for ground water, or in permanent draining systems for clean water, or handling solids in suspension. They are also ideal for pumping the sewage water from collecting sumps into which dishwashers or washing machines are discharging. For high temperature hot water in the industrial and commercial field we recommend the use of our US 73 and US 103 HE/HES.


This range of pumps is suitable for stationary and portable use. For easy removal of the pumps from deep sumps we recommend the use of our guide rail systems which provide ease of maintenance and inspection.

For automatic monitoring of the oil chamber a seal leak control can be connected.

Maximum cable length of the pumps is 10 m. 3-phase pumps with level control (US 151 DS, US 152 DS and US 251 DS) have a CEE-Plug with phase inverter.

The sewage pumps are tested by the German Institute for Construction Engineering and correspond to the valid construction and test principles.

#### PERFORMANCE



Type	Delivery head H [m]	1	2	3	4	5	6	7	8	9	10	11	12	13	14	16
US 62 E/ES	Flow rate Q [m³/h]	19	17	15	12	10	8	6	4	2						
US 62 D/DS		22	20	17	15	12	10	8	6	4						
US 102 E/D/ES/DS		28	26	23	21	19	17	15	12	10	8	5	2			
US 152 E/ES		30	29	27	24	22	20	18	15	13	11	8	6	3	1	
US 152 D/DS		31	30	28	26	23	21	19	17	14	12	10	8	5	3	
US 151 E/D/ES/DS		40	39	37	35	33	31	29	26	23	20	17	14			
US 251 D/DS		54	52	51	49	47	45	43	40	38	35	32	29	25	21	10

We reserve the right to change specifications without notice. Pump performance is subject to ISO 9906 tolerances

The minimum flow velocity in the pressure piping must be 0.7 m/s according to EN 12056. This data is represented in the performance curve as a limit of application.



# US 62–US 251

## SUBMERSIBLE DRAINAGE PUMPS

### SCOPE OF SUPPLY

Pump according to DIN EN 12050 ready for connection with 10 m cable. US 62 and US 102 with safety plug (1-phase) or CEE-Plug (3-phase).

US 151, US 152 and 251: Pumps without level control with free lead end. Pump with built-in level control with CEE-Plug and phase inverter (3-phase) or safety-plug (1-phase).

### MECHANICAL DATA

Pump	Vertical single-stage	Oil chamber	Yes
Free passage	10 mm	Seal on medium side	SiC mechanical seal
Bearing	Ball bearings, grease-lubricated	Run dry protection	Yes
Seal on motor side	Duplex rotary shaft seals	Submersible	Yes
		Pressure outlet	IG 1 1/2" (US151,251: 2")

### ELECTRICAL DATA

Power line	10m H07RN-F	Insulation class	B (151,251:F)
Type of enclosure	IP 68	Winding thermostat	Yes

### US 62–US 251


Type	Code No.	Voltage	Motor rating P1	P2	Current	Wires	Motor protection	Plug	Weight
<b>Without level control</b>									
US 62 E	<b>JP09812</b>	1/N/PE~230 V	0.83 kW	0.50 kW	3.9 A	3G1,0	Integrated	Safety	12.6 kg
US 62 D	<b>JP09813</b>	3/PE~400 V	0.85 kW	0.60 kW	1.4 A	4G1,0	Integrated	CEE	12.8 kg
US 102 E	<b>JP09278</b>	1/N/PE~230 V	1.37 kW	0.98 kW	6.0 A	3G1,0	Integrated	Safety	14.5 kg
US 102 D	<b>JP00214</b>	3/PE~400 V	1.36 kW	1.06 kW	2.4 A	4G1,0	Integrated	CEE	15.0 kg
US 152 E	<b>JP09435</b>	1/N/PE~230 V	1.60 kW	1.21 kW	7.5 A	3G1,0	on request <sup>1</sup>	Without	16.0 kg
US 152 D	<b>JP09437</b>	3/PE~400 V	1.70 kW	1.41 kW	3.1 A	4G1,0	on request <sup>1</sup>	Without	17.0 kg
<b>With built-in level control</b>									
US 62 ES	<b>JP09814</b>	1/N/PE~230 V	0.83 kW	0.50 kW	3.9 A	3G1,0	Integrated	Safety	12.7 kg
US 62 DS	<b>JP09815</b>	3/PE~400 V	0.85 kW	0.60 kW	1.4 A	4G1,0	Integrated	CEE	12.9 kg
US 102 ES	<b>JP09279</b>	1/N/PE~230 V	1.37 kW	0.98 kW	6.0 A	3G1,0	Integrated	Safety	14.5 kg
US 102 DS	<b>JP00218</b>	3/PE~400 V	1.36 kW	1.06 kW	2.4 A	4G1,0	Integrated	CEE	15.0 kg
US 152 ES	<b>JP09436</b>	1/N/PE~230 V	1.60 kW	1.21 kW	7.5 A	3G1,0	Integrated	Safety	16.0 kg
US 152 DS	<b>JP09438</b>	3/PE~400 V	1.70 kW	1.41 kW	3.1 A	4G1,0	Integrated	CEE	17.0 kg
<b>Without level control</b>									
US 151 E	<b>JP09310</b>	1/N/PE~230 V	1.68 kW	1.19 kW	7.6 A	4G1,0	on request <sup>1</sup>	Without	27.0 kg
US 151 D	<b>JP09300</b>	3/N/PE~400 V	1.60 kW	1.30 kW	3.0 A	6G1,5	on request <sup>1</sup>	Without	27.5 kg
US 251 D	<b>JP09301</b>	3/N/PE~400 V	2.60 kW	2.10 kW	4.4 A	6G1,5	on request <sup>1</sup>	Without	27.5 kg
<b>With built-in level control</b>									
US 151 ES	<b>JP09241</b>	1/N/PE~230 V	1.68 kW	1.19 kW	7.6 A	4G1,0	Integrated	Safety	29.0 kg
US 151 DS	<b>JP09243</b>	3/N/PE~400 V	1.60 kW	1.30 kW	3.0 A	6G1,5	Integrated	CEE	29.5 kg
US 251 DS	<b>JP09245</b>	3/N/PE~400 V	2.60 kW	2.10 kW	4.4 A	6G1,5	Integrated	CEE	29.5 kg

<sup>1</sup>Protective motor plug necessary see accessory


# US 62-US 251

## SUBMERSIBLE DRAINAGE PUMPS


Dimensions and switching points US 62, US 102, US 152 (mm)




Dimensions US 151 and US 251 (mm)



Dimensions and switching points GR 40 (mm)




Dimensions GR 50 (mm)



# US 62-US 251


## SUBMERSIBLE DRAINAGE PUMPS

Example of single pump installation with GR



Single unit 1½" with GR 40: sump area min. 40x60 cm  
 Single unit 1½" without GR: sump area min. 40x40 cm  
 Single unit 2" with GR 50: sump area min. 40x70 cm  
 Single unit 2" without GR: sump area min. 40x50 cm  
 Duplex unit 1½" with GR 40: sump area min. 60x60 cm  
 Duplex unit 1½" without GR: sump area min. 40x60 cm  
 Duplex unit 2" with GR 50: sump area min. 70x70 cm

Example of duplex pump installation



Duplex unit 2" without GR: sump area min. 50x70 cm

In case of installation beneath the backpressure level the pressure tube must be taken in a loop over the local backup level acc. to EN 12056. Besides, it must be secured with an EN 12050-4-proofed swing-type check valve. Additionally we recommend an alarm system.

In accordance with EN 12056-4 section 5.1, it has a built-in automatic spare pump or a double attachment included, which ensures that sewage drainage is not interrupted.

Suspend control unit in a dry room







### MECHANICAL ACCESSORY

				Code No.
	<b>① Swing-type check valve</b>			
	R40 EN 12050-4	1½" (DN 40), PN 4	150x120 (HxB)	JP00317
	DR 40 EN 12050-4	1½" (DN 40), PN 4	200x280 (HxB)	JP09155
	R50 EN 12050-4	2" (DN 50), PN 4	150x120 (HxB)	JP00326
	<b>Ball-type check valve</b>			
	KE40 EN 12050-4	1½" (DN 40), PN 6	170x125 (HxB)	JP47974
	K50 EN 12050-4	2" (DN 50), PN 6	185x155 (HxB)	JP44782
	<b>② Stop valve</b>			
		brass, 1½" (DN 40), PN 16	125x60 (HxB)	JP44786
		brass, 2" (DN 50), PN 16	140x70 (HxB)	JP44787
	<b>③ Elastic connection</b>			
		1½" (DN 40), PN 4	120x50 (HxD)	JP44777
		2" (DN 50), PN 4	150x63 (HxD)	JP44775


# US 62-US 251

## SUBMERSIBLE DRAINAGE PUMPS

### MECHANICAL ACCESSORY

			Code No.
	<b>4</b> Hose band clamp	1½"	JP44763
		2"	JP44764
	<b>5</b> Elbow	1½"	JP45953
		2"	JP44771
	<b>6</b> Hose coupling		
	Coupling Storz C	1½" male thread	JP44770
	Coupling Storz C	2" male thread	JP50217
	Coupling wrench		JP25708
	<b>Pressure hose</b>		
		12,5 m, synthetic, with coupling Storz C, Ø 38 mm	JP50298
		15 m, synthetic, with coupling Storz C, Ø 52 mm	JP00336
	<b>7</b> Special float	for lower switching points	JP44795
	<b>8</b> Chain	certified, 2.5 m, 320 kg, 5 rings (EN 818 mod.)	JP45901
		certified, 5.0 m, 320 kg, 8 rings (EN 818 mod.)	JP45902
		certified, 7.5 m, 320 kg, 11 rings (EN 818 mod.)	JP47365
	<b>9</b> Webbing	with shackle	JP45168
	<b>10</b> Guide rail system		
		GR 40	JP25592
		GR 50	JP25593
	Guide rail 1"	1500 mm	JP48937
	Guide rail 1"	2000 mm	JP48938
	Guide rail 1"	2500 mm	JP48939
	Guide rail 1"	3000 mm	JP48940







### ELECTRICAL ACCESSORY

			Code No.
	<b>a</b> Alarm unit		
	AG3	subm. ball contact switch, mains dependent, potential-free contact, 3 m cable	JP44891
	AG10	subm. ball contact switch, mains dependent, potential-free contact, 9,5 m cable	JP44892
	<b>Washing machine stop</b>		
	AW3	subm. ball contact switch, mains dependent, 3 m cable	JP44895
	AW0	for alarm forwarding in case of several washing machines	JP44899

# US 62-US 251

## SUBMERSIBLE DRAINAGE PUMPS

### ELECTRICAL ACCESSORY

			Code No.
	<b>b Control for single units</b>		
	Control unit NE 1	230 V, subm. ball contact switch 3.0 m	JP16710
	Control unit NE 1A	230 V, subm. ball contact switch 3.0 m, alarm	JP16714
	Control unit NE 2	230 V, subm. ball contact switch 9.5 m	JP16711
	Control unit NE 2A	230 V, subm. ball contact switch 9.5 m, alarm	JP16715
	Control unit ND 1	400 V, subm. ball contact switch 3.0 m	JP16712
	Control unit ND 1A	400 V, subm. ball contact switch 3.0 m, alarm	JP16716
	Control unit ND 3	400 V, subm. ball contact switch 9.5 m	JP16713
	Control unit ND 3A	400 V, subm. ball contact switch 9.5 m, alarm	JP16717
		<b>Control for duplex units</b>	
Control unit BD 00 E		230 V, for pumps U3-U6, US 62-105, UV 300, 08/2 ME	JP45735
Control unit HIGHLOGO 2-00 E		230 V	JP47996
Control unit BD 00		400 V, for pumps U6, US 62-105, UV 300	JP45993
Control unit HIGHLOGO 2-00		400 V	JP47997
Control unit BD 25		400 V, for pumps US 151-155	JP45737
Control unit HIGHLOGO 2-25		400 V	JP47998
Control unit BD 610 EC		230 V, with operating capacitor	JP45743
Control unit BD 46		400 V, for pumps US 251-253, UV 620-3, UV 625-3	JP45739
Control unit HIGHLOGO 2-46		400 V	JP47999
	<b>Level control</b>		
	Subm. switch pack B	3 subm. ball contact switch with 9.5 m and fixing devices	JP16725
	Subm. switch pack BmG	3 subm. ball contact switch with 9.5 m and counterweight to stabilize the subm. ball contact switch	JP16726
	Weight		JP44803
	<b>Protective motor plug</b>		
	Safety protective motor plug	230 V (without level control)	JP40264
	Protective motor plug, 8 A	230 V, for pumps without integrated motor protection	JP44753
	CEE motor protection 2,5-4,0 A	400 V, mandatory for pumps without integrated motor protection	JP44754
	CEE motor protection 2,8-4,0 A	400 V, mandatory for pumps without integrated motor protection	JP44750
	CEE motor protection 4,0-6,0 A	400 V, mandatory for pumps without integrated motor protection	JP44751
	<b>c Rechargeable battery</b>	for mains independent alarm	JP44850
		<b>d Seal leak detector</b>	DKG
<b>e Smart Home</b>		FTJP radio transmitter	JP47209